

U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101
PHONE: (800) 860-1850 FAX: (901) 526-2339
Visit Our Website at www.usindustrial.com

Dear Customer,

We are pleased to offer for your consideration:

ONE (1) NEW U.S. INDUSTRIAL 88 TON X 8' HYDRAULIC PRESS BRAKE WITH FRONT OPERATED POWER BACKGAUGE AND POWER RAM ADJUST

Model Number: USHB88-8HM

STANDARD EQUIPMENT: (All of the following comes with the machine)

- Power Front Operated Back Gauge, motorized with fine adjustment handwheel
- Power Ram Depth Control, motorized with fine adjustment handwheel
- Digital Displays for backgauge position and ram position
- All Steel Construction
- Sick 4000 Light Curtain
- Ram accepts standard American Tang tooling, 1/2" x 5/8"
- Space between Ram Tool Clamps allows for deep box bending
- Bed has slot for standard American Tang tooling
- Bed also has capture clamps for tooling without tang
- Free Gooseneck Punch and multi-opening Die for up to 90° forming in 10 gauge mild steel
- (see note on page 2)

SPECIFICATIONS:

• Working Pressure:	88 Tons	• Pressing Speed:	Dependent on Tool Load
• Length of Working Table:	98.4"	• Hydraulic Oil Capacity:	60 Gal.
• Distance Between Housings:	81.8"	• Motor Horsepower:	10 HP
• Throat Depth:	9.8"	• Net Weight:	12,127 lbs.
• Stroke Adjustment of Ram:	1.96"	• Length:	120"
• Ram Travel:	3.93"	• Width:	64"
• Open Height:	13.7"	• Height:	90"
• Rapid Ram Travel Speed:	2.4"/sec.		
• Rapid Ram Retreat Speed:	2.0"/sec.		
• Backgauge Travel:	24"		

*** Continued on Page 2 ***

