P.O. BOX 2098 MEMPHIS, TN 38101

PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Website at www.usindustrial.com

Dear Customer: Visit Our Website at www.usindustrial.com

We are pleased to offer the following equipment for your consideration:

# ONE (1) NEW U.S. INDUSTRIAL 10" X 54" HEAVY DUTY MANUAL VARIABLE SPEED MILLING MACHINE

Model Number: 3VH-3-KIT

#### STANDARD FEATURES AND EOUIPMENT: (KIT PACKAGE ONLY)

- Large 10" x 54" table with 3 T-slots, 5/8", on 2.5" centers

  Table travel is 37.4". Leadscrew pitch is 5TPI with dials on each end graduated in .001".
- Large knee allows saddle to travel 16.5" for cross feed with .001" dial graduations
- Large knee travel is 16.5" with 10TPI leadscrew, .001" dial graduations
- Large ram allows for over 18.5" of travel, inlaid scale, and deep throat for large workpieces
- Large Square Ways on Y and Z Axis..... Double locks on all axis
- Aged stressed castings, stress relieved for long life and accuracy, Meehanite type
- Power quill feed allows for 0.0018, 0.003, 0.006 Inches of feed per revolution of spindle
- Hardened and ground and precisely scraped work table, saddle and knee ways, turcite B coated for wear resistance
- Centralized one-shot lubrication pump lubricates all way surfaces and leadscrews
- Backlash adjustment for leadscrews, Gib adjustments for ways
- Electrical cabinet with internal transformer for 110V and 24V devices, circuit breaker protected, Low Voltage controls, 24-volt halogen machine light.
  - Transformer also includes power supply for digital readout and power table feed.
- Operator low voltage controls for coolant pump, machine light, main power with emergency stop button. Spindle off/forward/reverse switch.
- Built in coolant tank base with coolant pump, pressure and return hose, nozzle and valve, Installed and ready to use. Base chip pan to help prevent coolant overflow.
- Manual variable speed spindle drive, 3 Horsepower runs the spindle from 60 to 4200 RPM.
   Spindle speed dial on head shows RPM in direct drive and back gear. Spindle motor is finned for cooling.
- **Sino** three axis digital readout has 0.0002" resolution. Readout comes mounted to knee, table and cross and is ready to use. The readout is inch/metric switchable, with absolute incremental function. There is a calculator function, bolt hole pattern function, line pattern function, and arc calculate function. A comprehensive manual is included.
- Power table feed is **Align** model AL500SP. Infinitely variable feed from .8 to 32 IPM with rapid button, on/off switch, and adjustable travel stops. This heavy-duty power feed has 150-inch pounds of torque, with max to 650. Power table feed comes installed on machine, ready to use.
- Toolbox and tools, manuals, electrical drawing, test certificate all included.



P.O. BOX 2098 MEMPHIS, TN 38101

PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Website at www.usindustrial.com

Page 2 - NEW U.S. INDUSTRIAL 10" X 54" HEAVY DUTY MANUAL VARIABLE SPEED MILLING MACHINE, Model Number: 3VH-3-KIT

### **SPECIFICATIONS:**

Working Surface  Longitudinal Travel	. 10" x 54" 34.4" with powerfeed (37.4" without powerfeed) (Powerfeed stops prevent overtravel)				
	<ul> <li>. 16.5" (15.5" with readout installed)</li> <li>. 16.5"</li> <li>. 18.5" with scale</li> <li>. 90 degrees left, 90 degrees right with degree ring scale</li> <li>. 45 degrees front, 45 degrees back with degree ring scale</li> <li>. 360 Degree with degree ring scale</li> </ul>				
Spindle Drive					
Spindle Range (Manual Vari-speed sheeve)60-4200 Variable with Direct Drive and Back-geared					
Spindle Type  Quill Travel & Diameter  Power quill feed range, Inches per rev  Weight of Work Piece, max  Spindle Motor	5" travel and 3 3/8" diameter 0.0018", 0.003", 0.006" 660 lbs				
Electrics.	.208-240V or 440/460/480V, 3 phase – pick one				
Machine, Net Weight	. 3400 lbs				

P.O. BOX 2098 MEMPHIS, TN 38101

PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Website at www.usindustrial.com

Page 3 - NEW U.S. INDUSTRIAL 10" X 54" HEAVY DUTY MANUAL VARIABLE SPEED MILLING MACHINE, Model Number: 3VH-3-KIT

#### Standard Configuration of KIT Machine: (All items already installed on machine!)

•	Price of machine KITF. O. B. Memphis, TN\$ Part Number: 3VH-3	16,990.00
•	Heavy duty power table feed on X axis	Included
	Part Number: AL500SP	
•	Flood coolant pump, hose, nozzle	Included
	Part Number FCKIT	
•	Chip pan	Included
	Part Number CPKIT	
•	Machine light	Included
	Part Number MLKIT	
•	Front and Rear way covers	Included
	Part Number: FRWCKIT	
•	Three axis digital readout	Included
	Part Number SINO3AX	
	- 51-5 - 51-51-52 - 62 - 62 - 62 - 62 - 62 - 62 - 62 -	

### TOTAL PRICE OF KIT......F.O.B. Memphis, TN......\$ 16,990.00

#### Options you may wish to purchase: (All items will be installed on machine.)

	Air Power Drawbar, pneumatic, installed	805.00	(PDB-PB001)
	· •		,
•	Bestline Power Feed for Y-axis (cross feed)		(Y150-3V)
•	Bestline Power Feed for Z-axis (knee feed)	840.00	(Z150-3V)
•	Mill QC collet set, 1 holder R-8 to ER32, 1 spanner for collet nut,		
	11 ER32 collets from 1/8" to 3/4", all in form fitted case	299.00	(R8ER32KIT-K)
•	Clamp kit, 58 piece, bolts, nuts, step blocks, fingers, for fixturing	119.00	(CK-K)
•	Precision Parallel Set, several matched parallels in form case	169.00	(P100-K)
•	Milling vise, 6" lock type	299.00	(6" VISE-K)
•	R-8 collet set, 11 pieces		(R8-SET)

We await your reply and thank you for this opportunity to quote.

Sincerely,

U.S. Industrial Machinery

\*\*\* PLEASE SEE NEXT PAGE FOR PHOTOS AND IMPORTANT INFORMATION \*\*\*

P.O. BOX 2098 MEMPHIS, TN 38101

PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Website at www.usindustrial.com

U. S. Industrial Machinery Vertical Milling Machine Model 3VH-3



Detail of work light, digital readout, collet rack, table feed, coolant nozzle, way cover, ram and spindle





SINO 3-Axis digital readout measure table, cross and knee travel, inch/metric, and multifunctionality



Electrical Cabinet –Control and accessory power transformer, circuit breakers and main disconnect.