

Visit Our Website at www.usindustrial.com

We are pleased to offer the following equipment for your consideration:

ONE (1) NEW U.S. INDUSTRIAL 9" X 49" MANUAL VARIABLE SPEED VERTICAL MILLING MACHINE

Model Number: 2VH-3

STANDARD FEATURES AND EQUIPMENT:

- 9" x 49" table with 3 T-slots, 5/8", on 2.5" centers Table travel is 33". Leadscrew pitch is 5TPI with dials on each end graduated in .001".
- Travel of cross feed is 12" with .001" dial graduations
- Knee travel is 15.74" with 10TPI leadscrew, .001" dial graduations
- Ram allows for over 12" of travel, for variable throat depth
- Conventional dovetail ways on X, Y and Z Axis...... Double locks on all axis
- Aged stressed castings, stress relieved for long life and accuracy, Meehanite type
- Power quill feed allows for 0.0018, 0.003, 0.006 Inches of feed per revolution of spindle
- Hardened and ground and precisely scraped work table, saddle and knee ways
- Centralized one-shot lubrication pump lubricates all way surfaces and leadscrews
- Backlash adjustment for leadscrews, Gib adjustments for ways
- Electrical cabinet with internal transformer for 110V and 24V devices, circuit breaker protected, Low Voltage controls, 24 volt halogen machine light.
 - Transformer also includes power supply for digital readout and power table feed.
- Operator low voltage controls for coolant pump, machine light, main power with emergency stop button. Spindle off/forward/reverse switch.
- Built in coolant tank base with coolant pump, pressure and return hose, nozzle and valve, Installed and ready to use. Base chip pan to help prevent coolant overflow.
- Manual variable speed spindle drive, 3 Horsepower runs the spindle from 60 to 4200 RPM.
 Spindle speed dial on head shows RPM in direct drive and back gear. Spindle motor is finned for cooling.
- **Sino** three axis digital readout has 0.0002" resolution. Readout comes mounted to knee, table and cross and is ready to use. The readout is inch/metric switchable, with absolute incremental function. There is a calculator function, bolt hole pattern function, line pattern function, and arc calculate function. A comprehensive manual is included.
- Power table feed is **Align** model AL500SP. Infinitely variable feed from .8 to 32 IPM with rapid button, on/off switch, and adjustable travel stops. This heavy duty power feed has 150 inch pounds of torque, with max to 650. Power table feed comes installed on machine, ready to use.
- Toolbox and tools, manuals, electrical drawing, test certificate all included.



U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101

PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Website at www.usindustrial.com

Page 2 - NEW U.S. INDUSTRIAL 9" X 49" MANUAL VARIABLE SPEED MILLING MACHINE, Model Number: 2VH-3-KIT

SPECIFICATIONS:

Working Surface	. 9" x 49"
Longitudinal Travel	
	(Powerfeed stops prevent overtravel)
Cross Travel	12" (11" with readout installed)
Vertical Travel	15.74
Ram Travel	12"
Head tilt, left to right	90 degrees left, 90 degrees right with degree ring scale
Head Tilt, front to back	. 45 degrees front, 45 degrees back with degree ring scale
Ram Circular Movement	. 360 Degree with degree ring scale
T-Slots	3 with 2 1/2" centers, 5/8" Ea.
Spindle Drive	. 3 HP
Spindle Range (Manual Vari-speed sheeve)	60-4200 Variable with Direct Drive and Back-geared
a . u .m	D 0
Spindle Type	
Quill Travel & Diameter	5" travel and 3 3/8" diameter
Quill Travel & Diameter Power quill feed range, Inches per rev	5" travel and 3 3/8" diameter0.0018", 0.003", 0.006"
Quill Travel & Diameter Power quill feed range, Inches per rev Weight of Work Piece, max	5" travel and 3 3/8" diameter0.0018", 0.003", 0.006"500 lbs
Quill Travel & Diameter Power quill feed range, Inches per rev	5" travel and 3 3/8" diameter 0.0018", 0.003", 0.006" 500 lbs 3 HP, 208-240 volt or 440/460/480
Quill Travel & Diameter Power quill feed range, Inches per rev Weight of Work Piece, max	5" travel and 3 3/8" diameter 0.0018", 0.003", 0.006" 500 lbs 3 HP, 208-240 volt or 440/460/480 volt, 3 phase spindle motor motor-
Quill Travel & Diameter Power quill feed range, Inches per rev Weight of Work Piece, max	5" travel and 3 3/8" diameter 0.0018", 0.003", 0.006" 500 lbs 3 HP, 208-240 volt or 440/460/480
Quill Travel & Diameter Power quill feed range, Inches per rev Weight of Work Piece, max Spindle Motor	5" travel and 3 3/8" diameter 0.0018", 0.003", 0.006" 500 lbs 3 HP, 208-240 volt or 440/460/480 volt, 3 phase spindle motor motor- standard
Quill Travel & Diameter Power quill feed range, Inches per rev Weight of Work Piece, max Spindle Motor	5" travel and 3 3/8" diameter 0.0018", 0.003", 0.006" 500 lbs 3 HP, 208-240 volt or 440/460/480 volt, 3 phase spindle motor motor-
Quill Travel & Diameter Power quill feed range, Inches per rev Weight of Work Piece, max Spindle Motor	5" travel and 3 3/8" diameter 0.0018", 0.003", 0.006" 500 lbs 3 HP, 208-240 volt or 440/460/480 volt, 3 phase spindle motor motor- standard
Quill Travel & Diameter	5" travel and 3 3/8" diameter0.0018", 0.003", 0.006"500 lbs 3 HP, 208-240 volt or 440/460/480 volt, 3 phase spindle motor motor- standard208-240V or 440/460/480V, 3 phase – pick one
Quill Travel & Diameter Power quill feed range, Inches per rev Weight of Work Piece, max Spindle Motor	5" travel and 3 3/8" diameter0.0018", 0.003", 0.006"500 lbs 3 HP, 208-240 volt or 440/460/480 volt, 3 phase spindle motor motor- standard208-240V or 440/460/480V, 3 phase – pick one
Quill Travel & Diameter	5" travel and 3 3/8" diameter0.0018", 0.003", 0.006"500 lbs 3 HP, 208-240 volt or 440/460/480 volt, 3 phase spindle motor motor- standard208-240V or 440/460/480V, 3 phase – pick one

^{***} Continued on Page 3 ***

U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101 PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Website at www.usindustrial.com

Page 3 - NEW U.S. INDUSTRIAL 9" X 49" MANUAL VARIABLE SPEED MILLING MACHINE, Model Number: 2VH-3-KIT

Standard Configuration of KIT Machine: (All items already installed on machine!)

Price of machine KITF. O. B. Memphis, TN\$ Part Number: 2VH-3	13,990.00
Heavy duty power table feed on X axis	Included
Part Number: AL500SP	Included
Flood coolant pump, hose, nozzle Part Number FCKIT	meruded
Chip pan	Included
Part Number CPKIT Machine light Part Number MLKIT	Included
Front and Rear way covers Part Number: FRWCKIT	Included
• Three axis digital readout	Included
Part Number SINO3AX	
TOTAL PRICE OF KIT	13,990.00
	13,990.00
TOTAL PRICE OF KITF.O.B. Memphis, TN\$	
TOTAL PRICE OF KITF.O.B. Memphis, TN\$ Options you may wish to purchase: (All items will be installed on machine.)	\$895.00 (UPM1501)
TOTAL PRICE OF KIT	\$895.00 (UPM1501)
TOTAL PRICE OF KIT	\$895.00 (UPM1501) \$760.00 (UPM1502) \$840.00 (UPM1503)
TOTAL PRICE OF KIT	\$895.00 (UPM1501) \$760.00 (UPM1502) \$840.00 (UPM1503)

We await your reply and thank you for this opportunity to quote.

Sincerely,

U.S. Industrial Machinery

*** SEE NEXT PAGE FOR PHOTOS AND IMPORTANT INFORMATION **


U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101

PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Website at www.usindustrial.com

U. S. Industrial Machinery Vertical Milling Machine Model 2VH-3







functionality

