U.S. INDUSTRIAL MACHINERY, INC.

P.O. BOX 2098 MEMPHIS, TN 38101 FAX: (901) 526-2339 PHONE: (800) 860-1850

Visit Our Website at www.usindustrial.com

Dear Customer,

We are pleased to offer for your consideration:

ONE (1) NEW U.S. INDUSTRIAL 88 TON X 10' **HYDRAULIC PRESS BRAKE**

Model Number: USHB88-10C



- Ram Deflection Adjustment
- Massive Torsion Bar for Parallelism
- Three Speed Ram
- Bottom Time Delay
- Inching, Single Cycle and Auto Run
- Bed tools are held with standard slot for ½" x 5/8" tang w/set screws, plus die clamps are included

24"

• Ram takes standard American Tang Tooling (1/2" x 5/8") and American Safety Tang Tooling, and Z1

All Steel Construction

- Space between Ram Tool Clamps allows for deep box bending
- Free Gooseneck Punch and multi-opening Die for up to 90° forming up to 10-gauge mild steel (see note on page 2)

SPECIFICATIONS:

88 Tons	Pressing Speed:	Dependent on Tool Load
125.9"	 Hydraulic Oil Capacity: 	79 Gal.
106.2"	Motor Horsepower:	10 HP, 220 or 440 Volts, 3 ph.
		35/17.5 amp
9.8"	Net Weight:	14,332 lbs.
1.96"	Length:	148"
3.93"	• Width:	64"
13.7"	• Height:	90"
2.4"/sec.		
2.0"/sec.		
	125.9" 106.2" 9.8" 1.96" 3.93" 13.7" 2.4"/sec.	 125.9" Hydraulic Oil Capacity: Motor Horsepower: 9.8" Net Weight: 1.96" Length: 3.93" Width: 13.7" Height: 2.4"/sec.

^{*}specifications are subject to change without notice

· Backgauge Travel:


Forged Heavy Duty Cylinder and Cylinder Body

Rapid Approach, Bending Cycle and Rapid Retreat

^{***} Continued on Page 2 ***


IMPORTANT FEATURES INCLUDED WITH U.S. INDUSTRIAL PRESS BRAKES:


- Special Note: The Gooseneck Punch and multi-opening Die included are general purpose tools to be used for training. Precision tooling should be purchased to meet your specific needs. The punch is segmented and it is up to the customer to calibrate these if they want to use them for a particular purpose.
- * There is no warranty on this tooling.




Gooseneck Punch Tool Sections included, full length of Ram. Multi-opening V-Die for up to 90 degree forming included, full length of bed. Die lifting rings included.


Our Standard Ram Clamps and Optional cam-lever Ram Clamps will hold all Punch Tangs shown below:








Our **bed** has slot for the Standard Die Tang as shown below. Also, bed tooling without tang can be held with the included capture clamps.







Our **optional** ram clamps for all punch Tangs shown above. Lever action allows for quick tool change.



TOTAL – Normal Stock or Short Delivery Configuration F.O.B. MEMPHIS \$ 54,985.00

AVAILABLE OPTIONS:

CNC 2-Axis Color Graphic Control:	Shown above
Controls BOTH Bend Angle and Backgauge Position. Comes with 6" LCD touch screen. Code	
and Graphic programming included. Graphic allows 10 bends per program/cross-section. Controls	
features a tool library, Metric/inch switchable, Auto bend sequence, Auto retract of Backgauge, Spread	
length, Interference bend alert, Calculated bend allowance, Programmable ram dwell and much more.	
Control stores thousands of programs with USB Port, Ethernet and RS232 for program backup.	
Sick Model deTec 4 Light Curtain System – Minimum OSHA Requirement	Shown above
 Upgrade to Fiessler Akas II Laser Guarding (Substitute for Sick deTec 4) 	\$9,995.00
A 11-11 1 A 1 (D. 1 A)	A

Add Third Axis (Back Gauge Height controlled from operator panel.)
 CNC Controlled Mechanical Auto Crown:
 Upgrade to Cam-Lever Quick Action Ram Clamps
 Training in our Memphis, TN Facility
 Training at customer site, less than 300 miles from Memphis:
 \$4,995.00
 \$5,295.00
 No Charge
 \$3,495.00

• Training at customer site, more than 300 miles from Memphis: (If outside continental USA, please call for quote.)

Press Brake CNC operators panel with LCD touch screen and graphics function





\$4,995.00

We await your reply and thank you for this opportunity to quote

U.S. INDUSTRIAL MACHINERY