U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101
PHONE: (800) 860-1850 FAX: (901) 526-2339
Visit Our Website at www.usindustrial.com

Dear Customer,



Model Number: USR825

STANDARD EQUIPMENT: (All of the following comes with the machine)

- Heavy duty gear-motor drives top and bottom pinch rolls
- Powered Bending Roll Adjustment and Manual Precision Pinch Roll Adjustment
- Emergency Trip Line
- Pedestal Control
- Quick Roll Adjustment
- Roll Position Indicators
- Crowned Rolls
- Low Voltage Push Button Controls
- · Machine is usually stocked with optional hydraulic swing-out feature for top roll
- · Machine is usually stocked with optional digital display with memory for position of bending roll
- Machine is usually stocked with optional ability to tilt rolls, and blocker for making tapered cones
- · Machine is usually stocked with optional hardened rolls and black oxide coated

SPECIFICATIONS:

Capacity: 8' x 1/4" Mild Steel @ 65000 PSI
Pre-Bend Capacity: 1/4" Mild Steel @ 65000 PSI

Top & Bottom Roll Diameter: 7.4"/7.5" (ends/middle)
Bending Roll Diameter: 6.67"/7.1" (ends/middle)

• Speed: 12. 5 FPM

• Main Drive Motor: 5.5 HP Reduction Gear Drive

Adjustment Motor for bend roll position 3 HP
Machine Length: 160"

Machine Width: 54"Machine Height: 44"

• Net Weight: 8,025 lbs.

• Voltage: 220/440 Volts, 3 Phase

^{*}specifications are subject to change without notice

(The above configuration is usually in stock in Memphis, TN. Please check delivery at time of order.)

We await your reply and thank you for this opportunity to quote.

U.S. INDUSTRIAL MACHINERY

